

NEW SECURPATCHPLUS



**Macchina rotativa bobina-bobina per applicazione
a caldo di bollini olografici tramite sistema stop&go.
Questo modello, estremamente innovativo, è tecnologicamente
più avanzato e consente di incrementare la produttività.**

*Rotary reel to reel machine for the hot stamping
of hologram patches through stop&go system.
This model is extremely innovative, and is technologically advanced.
It increases productivity.*

Caratteristiche tecniche :

- Passaggio carta : 520 mm.
- Diametro max. bobine : 1270 mm.
- Velocità max. di produzione : 60 battute/mio
- Grammatura carta : 60/150 gr/m2
- Distanza min. trasversale di applicazione bollini:
80 mm.
- Formato in dotazione : 24"
- bollini applicati ogni singola battuta:16
- Applicazione a registro programmabile da
pannello operatore

Technical Features :

- Paper path: 520 mm.
- Max. reels diameter: 1270 mm.
- Max. production speed: 60 strokes/min
- Paper grammage: 60/150 gr/m2
- Application distance between flanked patches:
80 mm.
- Size in endowment: 24"
- Patches transferred each stroke: 16
- Register application programmable
from operator panel.

NEW MEC S.r.l.
Via Beato Angelico, 21
20900 Monza (MB) - ITALY

Tel. ++39/039.2024452 r.a.
Fax ++39/039.2024483
e.mail info@newmec.it
site www.newmec.it